

AL-TR-1991-0065



AD-A239 559



A
R
M
S
T
R
O
N
G

STATPLOT STATISTICAL PLOTTING PROGRAM

John F. Seibert, Major, USAF, BSC

OCCUPATIONAL AND ENVIRONMENTAL
HEALTH DIRECTORATE
Brooks AFB TX 78235-5000

L
A
B
O
R
A
T
O
R
Y

July 1991

Final Technical Report

DTIC
ELECTED
AUG 20 1991
S B D

Approved for public release; distribution is unlimited.

91-08166



AIR FORCE SYSTEMS COMMAND
BROOKS AIR FORCE BASE, TEXAS 78235-5000

91 8 19 042

NOTICES

When Government drawings, specifications, or other data are used for any purpose other than in connection with a definitely Government-related procurement, the United States Government incurs no responsibility or any obligation whatsoever. The fact that the Government may have formulated or in any way supplied the said drawings, specifications, or other data, is not to be regarded by implication, or otherwise in any manner construed, as licensing the holder or any other person or corporation; or conveying any rights or permission to manufacture, use, or sell any patented invention that may in any way be related thereto.


The mention of trade names or commercial products in this publication is for illustration purposes and does not constitute endorsement or recommendation for use by the United States Air Force.

The Office of Public Affairs has reviewed this report, and it is releasable to the National Technical Information Service, where it will be available to the general public, including foreign nationals.

This report has been reviewed and is approved for publication.

Government agencies and their contractors registered with Defense Technical Information Center (DTIC) should direct requests for copies to: DTIC, Cameron Station, Alexandria VA 22304-6145.

Non-Government agencies may purchase copies of this report from: National Technical Information Service (NTIS), 5285 Port Royal Road, Springfield VA 22161.



JOHN F. SEIBERT, Maj, USAF, BSC
Chief, Industrial Hygiene Branch



MARK H. STOKES, Col, USAF, BSC
Deputy Chief, Occ Med Division

REPORT DOCUMENTATION PAGE

*Form Approved
OMB No. 0704-0188*

Public reporting burden for this collection of information is estimated to average 1 hour per response, including the time for reviewing instructions, searching existing data sources, gathering and maintaining the data needed, and completing and reviewing the collection of information. Send comments regarding this burden estimate or any other aspect of this collection of information, including suggestions for reducing this burden, to Washington Headquarters Services, Directorate for Information Operations and Reports, 1215 Jefferson Davis Highway, Suite 1204, Arlington, VA 22202-4302, and to the Office of Management and Budget, Paperwork Reduction Project (0704-0188), Washington, DC 20503.

1. AGENCY USE ONLY (Leave blank)			2. REPORT DATE July 1991		3. REPORT TYPE AND DATES COVERED Final		
4. TITLE AND SUBTITLE STATPLOT Statistical Plotting Program			5. FUNDING NUMBERS				
6. AUTHOR(S) John F. Seibert							
7. PERFORMING ORGANIZATION NAME(S) AND ADDRESS(ES) Armstrong Laboratory Occupational and Environmental Health Directorate Brooks AFB TX 78235-5000 (Formerly: AF Occupational and Environmental Health Laboratory (AFOEHL))			8. PERFORMING ORGANIZATION REPORT NUMBER AL-TR-1991-0065				
9. SPONSORING / MONITORING AGENCY NAME(S) AND ADDRESS(ES)			10. SPONSORING / MONITORING AGENCY REPORT NUMBER				
11. SUPPLEMENTARY NOTES							
12a. DISTRIBUTION / AVAILABILITY STATEMENT Approved for public release; distribution is unlimited.			12b. DISTRIBUTION CODE				
13. ABSTRACT (Maximum 200 words) Base bioenvironmental engineering (BEE) shops perform statistical analysis on industrial hygiene and environmental sample results by calculating the mean, standard deviation and 95% confidence intervals. However, these calculations assume the sample data follows a normal (Gaussian) distribution. Data should be analyzed for the distribution to be sure the proper statistics are being used. This technical report describes the microcomputer program "STATPLOT" written in BASIC, which plots sample results on linear vs. probability axes and on logarithmic vs. probability axes. Sample results which follow a normal (Gaussian) distribution will appear as a straight line on the linear vs. probability plot. Sample results which are log normal will appear as a straight line on the logarithmic vs. probability plot. STATPLOT is provided for use by all BEE shops in reviewing the statistical distribution of sample data (univariate analysis).							
14. SUBJECT TERMS Statistical analysis Statistical plotting <u>Normal distribution</u>			Gaussian distribution log normal distribution STATPLOT BASIC		15. NUMBER OF PAGES 34		
					16. PRICE CODE		
17. SECURITY CLASSIFICATION OF REPORT Unclassified		18. SECURITY CLASSIFICATION OF THIS PAGE Unclassified		19. SECURITY CLASSIFICATION OF ABSTRACT Unclassified		20. LIMITATION OF ABSTRACT UL	

CONTENTS

	Page
INTRODUCTION	1
DISCUSSION	1
RECOMMENDATION	3
REFERENCES	3
APPENDIX	
A Sample STATPLOT Output of Noise Dosimetry Data	5
B Plot of Normal (Gaussian) Data	9
C Plot of Lognormal Data	13
D Plot of Bimodal Distribution	17
E STATPLOT Program Listing	19
DISTRIBUTION LIST	25



Accession For	
NTIS GRA&I	<input checked="" type="checkbox"/>
DTIC TAB	<input type="checkbox"/>
Unannounced	<input type="checkbox"/>
Justification _____	
By _____	
Distribution/ _____	
Availability Codes	
Dist	Avail and/or Special
A-1	

STATPLOT STATISTICAL PLOTTING PROGRAM

INTRODUCTION

Purpose

This technical report describes the microcomputer program "STATPLOT" written in an IBM compatible BASIC which plots sample results on linear vs. probability axes and on logarithmic vs. probability axes. Sample results which follow a "normal" (Gaussian) distribution will appear as a straight line on the linear vs. probability plot. Sample results which are "log normal" will appear as a straight line on the logarithmic vs. probability plot.

Problem

Base Bioenvironmental Engineering (BEE) shops perform statistical analysis on industrial hygiene and environmental sample results by calculating the mean, standard deviation, and 95% confidence intervals. However, these calculations assume the data follows a normal (Gaussian) distribution. Past studies have shown industrial hygiene air sampling data is log normally distributed (1). No studies have proven the distribution for noise, radiation or environmental sampling (2). Data should be analyzed for a normal distribution to be sure the proper statistics are being used. While microcomputer statistical programs are widely available (SAS, SPSS, SYSTAT, MINITAB), they are not generally purchased or used by base level BEE offices.

Scope

STATPLOT is provided for use by all BEE shops in reviewing the statistical distribution of sampling data (univariate analysis). A full discussion of statistical data analysis is beyond the scope of this report and is not provided. Texts and night classes in statistics are widely available and recommended.

DISCUSSION

Theory of Operation

The BASIC program STATPLOT reads sample values from an ASCII text file, with one sample value per line of text. The values are sorted in decreasing order and printed out on a 80-column printer to show the operator the values used for its analysis (Appendix A). Starting on a new page, STATPLOT prints a one-page plot with linear vs. cumulative probability axes. The data points are plotted as '0's, and a straight line which shows how the data would be plotted if it followed a normal distribution is plotted as a series of '/'. A summary of sample statistics which assume the data is normally distributed is printed at the bottom of the plot. STATPLOT then takes the logarithm (base

ten) of all data points and prints a second plot and statistical analysis assuming the data is log normally distributed.

Using STATPLOT

Place data to be analyzed into a file as ASCII text with one data point per line. This can be done directly from MSDOS EDLIN, by converting a word processor text file to ASCII (usually as a utility or option on most word processing programs), or by printing the data from a spreadsheet directly to a file instead of the printer.

Copy STATPLOT into the same directory as the BASIC you use (TURBO BASIC, BASICA, GWBASIC).

Start your BASIC program. Type the commands <LOAD "STATPLOT"> and then <RUN>.

Turn on the printer connected to the computer and position the paper to the top of a page.

Answer the program prompt with the name of the file containing the data to be analyzed and the desired title to describe the plots.

Wait for the program to sort and plot the data. Three pages will be printed for each data set analyzed.

Interpreting Plots

Best Fit: Comparing plotted data to a straight line for the normal and log normal plots indicates which distribution the data follows. Appendix A shows real noise dosimetry data for Dover AFB forklift operators plotted on normal and log normal plots. While the data appears to better fit a normal plot, either plot could be used. Note that this log normal plot lists a Geometric Standard Deviation (GSD) of 1.08. This is well below the typical GSD of 1.5 to 2.0 for chemical exposures (3). (The GSD is a measure of the variability of data for a log normal distribution, in the same way the standard deviation describes variability for a normal distribution.) For such low GSDs, data appears to fit normal and log normal plots equally well. Appendix B shows normal (Gaussian) distributed data plotted on normal and log normal plots. Note that the normally distributed data appears curved on a log normal plot. Appendix C shows log normal distributed data plotted on normal and log normal plots. Log normally distributed data also appears curved on a normal plot.

Bimodal Distributions: A data set sometimes includes sample results from two groups of data, each with their own mean and standard deviation (or geometric mean and GSD). This can occur because the surveyor does not recognize the different job tasks or potentials for exposure. (Example: Noise exposures for tool crib operators vs. engine mechanics.) This will appear on a normal or log normal plot as an S-shaped curve or curve with two straight ends connected by a rounded elbow. The two underlying distributions can be estimated (with an active imagination, a straight ruler and a sharp pencil) as

the asymptotes of the ends of the curve. Appendix D shows a bimodal normal distribution as plotted with STATPLOT.

Confidence Intervals: Means and confidence intervals for the data can be read directly from the desired plot. The mean is read by finding the point on the graph aligned with the position for 50% probability. The upper 95% confidence limit is read at the 95% probability position.

Number of Samples: Trying to perform statistical analysis on one sample result will cause STATPLOT to abort. Analyzing only two sample results will give what appears to be a perfect fit of the data to both normal and log normal distributions. However, this is only a demonstration of the rule of geometry where any two points define a straight line, and should not be interpreted as having collected reliable data. As the number of samples approaches 10 or 15 samples, the ability to view the underlying statistical distribution improves.

RECOMMENDATION

Use STATPLOT to plot sampling data before making assumptions about the statistical distribution or calculating 95% confidence intervals.

REFERENCES

1. Leidel, N.A., K.A. Busch and W.E. Crouse, Exposure Measurement, Action Level and Occupational Environmental Variability. National Institute of Occupational Safety and Health (NIOSH), DHEW (NIOSH) Pub. No. 76-131 (1975)
2. Leidel, N.A., K.A. Busch and J.R. Lynch, Occupational Exposure Sampling Strategy Manual. National Institute of Occupational Safety and Health (NIOSH), DHEW (NIOSH) Pub. No. 77-173 (1977)
3. American Conference of Governmental Industrial Hygienists, Inc. (ACGIH), Threshold Limit Values for Chemical Substances and Physical Agents and Biological Exposure Indices. Cincinnati OH, 1990-1991 ed., (1990)

APPENDIX A

Sample STATPLOT Output of Noise Dosimetry Data


SAMPLE PRINTOUT

Data points from file: b:forklift.dat

67.3
70.4
71.2
72
72.1
73.2
76.8
77.5
78.7
79.5
79.6
80.3
80.6
80.7
80.8
81.2
81.7
82.4
82.9
83.9
84.2
86.8
87.4
92.1
93.7
95.1
104.3


Data in DESCENDING order is:

104.3
95.1
93.7
92.1
87.4
86.8
84.2
83.9
82.9
82.4
81.7
81.2
80.8
80.7
80.6
80.3
79.6
79.5
78.7
77.5
76.8
73.2
72.1
72
71.2
70.4
67.3



'//' = normal (Gaussian) distribution based on the statistics of the data
 Mean = 81.34815 Std.Dev = 8.27319
 '0' = data points

LOG (base 10) of DATA POINTS vs. CUMULATIVE PROBABILITY
 Forklift Operator Noise Dosimetry




'// = Log-Normal distribution based on the statistics of the LOGed data

Geometric Mean = $10^{\log_{10}(1.908257)} = 80.95736$

Geometric Std.Dev (GSD) = $10^{\log_{10}(4.311791E-02)} = 1.104379$


'0' = LOGed (base 10) data points

APPENDIX B
Plot of Normal (Gaussian) Data



'/' = normal (Gaussian) distribution based on the statistics of the data
 Mean = 80 Std.Dev = 19.31321
 '0' = data points

LOG (base 10) of DATA POINTS vs. CUMULATIVE PROBABILITY
 Normal (Gaussian) Distributed Data Mean 80 Std Dev 20




'/' = Log-Normal distribution based on the statistics of the LOGed data

Geometric Mean = $10^{1.892507}$ = 78.07403

Geometric Std.Dev (GSD) = $10^{.1085414}$ = 1.28393

'0' = LOGed (base 10) data points


APPENDIX C
Plot of Lognormal Data



'/' = normal (Gaussian) distribution based on the statistics of the data

Mean = 119.6 Std.Dev = 79.04935

'0' = data points



'// = Log-Normal distribution based on the statistics of the LOGed data


Geometric Mean = $10^1.999721 = 99.93582$

Geometric Std.Dev (GSD) = $10^{.2960732} = 1.977303$

'0' = LOGed (base 10) data points

APPENDIX D
Plot of Bimodal Distribution

LINEAR vs. CUMULATIVE PROBABILITY
Bimodal Distribution with Means at 60 and 90



'/' = normal (Gaussian) distribution based on the statistics of the data
 Mean = 75 Std.Dev = 17.41009
 '0' = data points

APPENDIX E
STATPLOT Program Listing

```

10  ' STATPLOT program to graphically print sampling results on
20  ' LINEAR vs PROBABILITY axes for a normal (Gaussian) distribution, and
30  ' LOG vs PROBABILITY axes for a log normal frequency distribution.
40  'Written by Maj John Seibert, AL/OEMI, Industrial Hygiene Branch, 4 Jan 91
50  'Please send any suggested changes to AL/OEMI, Brooks AFB TX 78235
60  ' DSN 240-3214
70  'File FORKLIFT included on this disk as a sample input data file
80  '
90  DIM A(500)           'A() contains the data points
100  DIM L$(51),YSCALE$(51)   'L$ contains plot lines, YSCALE$ is y-axis
110  '                      probability labels
120  '
130  'Read in Data from disk file
140  '
150  CLS :PRINT :PRINT
160  PRINT "          Be sure the printer is on and ON LINE" :PRINT :PRINT
170  PRINT "          Data points should be ready in a disk file,""
180  PRINT "          one data point per line." :PRINT :PRINT
190  PRINT "          Negative and zero values will be ignored." :PRINT
200  INPUT "          File name of data to be plotted";REC$
210  PRINT:INPUT"    Title of data to use as X-axis label";TITLE$
220  OPEN "I",#1,REC$
230  NPTS = 1
240  INPUT #1, A(NPTS)
250  IF EOF(1) THEN 290
260  IF A(NPTS) <= 0 THEN 240  'Throw out zero and negative values
270  NPTS = NPTS + 1
280  GOTO 240
290  CLOSE
300  '
310  'Print data points read in from file
320  '
330  LPRINT :LPRINT"  Data points from file: ";REC$ :LPRINT
340  FOR I = 1 TO NPTS
350  LPRINT A(I),
360  NEXT I
370  '
380  ' Sort data points in descending order to get ready for
390  ' cumulative probability distribution plotting
400  '
410  I = 1
420  IF I = NPTS GOTO 500
430  IF A(I) >= A(I+1) GOTO 480      'Consecutive values in correct order
440  SMALLER = A(I)
450  A(I) = A(I+1)
460  A(I+1) = SMALLER
470  GOTO 410
480  I = I + 1
490  GOTO 420
500  '
510  LPRINT:LPRINT"Data in DESCENDING order is: "
520  FOR I = 1 TO NPTS
530  LPRINT A(I),
540  NEXT I

```

```

550 LPRINT:LPRINT
560 '
570 'Prepare probability labels for Y-axis
580 '
590 FOR I = 1 TO 51
600   YSCALE$(I) = SPACE$(6)      'First fill each label with 6 blanks
610 NEXT I
620 YSCALE$(1)="      1":YSCALE$(4)="      2":YSCALE$(8)="      5"
630 YSCALE$(12)="     10":YSCALE$(17)="     20":YSCALE$(20)="     30"
640 YSCALE$(23)="Y     40":YSCALE$(26)="L     50":YSCALE$(29)="A     60"
650 YSCALE$(32)="R     70":YSCALE$(35)="     80":YSCALE$(40)="     90"
660 YSCALE$(44)="     95":YSCALE$(48)="     98":YSCALE$(51)="     99"
670 YSCALE$(33)="P      ":YSCALE$(31)="0      ":YSCALE$(30)="B      "
680 YSCALE$(28)="B      ":YSCALE$(27)="I      ":YSCALE$(25)="I      "
690 YSCALE$(24)="T      ":YSCALE$(21)="%"      "
700 '
710 'Start with NORMAL (Gaussian) plot
720 '
730 LPRINT CHR$(12)           'Page feed
740 LPRINT "                  LINEAR vs. CUMULATIVE PROBABILITY"
750 GOSUB 1050    'GOSUB CALC_POS to plot axis and data positions
760             'and print the body of the plot
770 '
780 'Print a footnote to the Plot
790 LPRINT "  '' = normal (Gaussian) distribution based on the ";
800 LPRINT "statistics of the data"
810 LPRINT "      Mean = ";MEAN;"      Std.Dev = ";STDDEV
820 LPRINT "  '0' = data points
830 '
840 ' LOG-NORMAL plot
850 '
860 'Take log base 10 of all data points, and
865 ' use the CALC_POS subroutine again
870 '
880 FOR I = 1 TO NPTS
890   A(I) = LOG(A(I))/LOG(10)    'LOG function is base e. This formula gives
900 NEXT I                      'the base 10 log.
910 LPRINT CHR$(12)           'Page feed
920 LPRINT "                  LOG (base 10) of DATA POINTS vs. CUMULATIVE PROBABILITY"
930 GOSUB 1050    'GOSUB CALC_POS to plot axis and data positions
940             'and print the body of the plot
950 '
960 'Print a footnote to the Plot
970 LPRINT "  '' = Log-Normal distribution based on the";
980 LPRINT "statistics of the LOGed data"
990 LPRINT "      Geometric Mean = 10^";MEAN;" = ";10^MEAN
1000 LPRINT "      Geometric Std.Dev (GSD) = 10^";STDDEV;" = ";10^STDDEV
1010 LPRINT "  '0' = LOGed (base 10) data points"
1020 LPRINT CHR$(12)           'Page feed
1030 STOP
1040 '
1050 'Subroutine CALC_POS to calculate axis and data positions
1060 '
1070 '

```

```

1080 'Calculate Statistics
1090 '
1100 AMAX = A(1): AMIN = A(NPTS)      'Know min & max, since already sorted
1110 SUM = 0
1120 FOR I = 1 TO NPTS
1130   SUM = SUM + A(I)
1140 NEXT I
1150 MEAN = SUM/NPTS
1160 '
1170 DIFF = 0
1180 FOR I = 1 TO NPTS
1190   DIFF = DIFF + (A(I)-MEAN)^2
1200 NEXT I
1210 STDDEV = SQR(DIFF/(NPTS-1))
1220 '
1230 'Calculate x-axis scale min and max based on input data
1240 XINTERV = 10^(INT(LOG(AMAX)/LOG(10))-1)  'One factor of 10 below AMAX
1250 XMIN = XINTERV * INT(AMIN/XINTERV)          'Interval multiple below
1260 XMAX = XINTERV * INT((AMAX+XINTERV)/XINTERV) 'Interval multiple above
1270 '
1280 'Prepare plot lines L$(1) through L$(51) for data
1290 FOR I = 1 TO 51
1300   L$(I) = "I" + STRING$(69," ") + "I"      '71 print positions per line
1310 NEXT I
1320 L$(1) = STRING$(71,"-")      'L$(1) and L$(51) are x-axis at top and bottom.
1330           '1st character is at zero position on y-axis.
1340           '71st character is at full scale position.
1350 '
1360 SCALE$ = SPACE$(75)      'SCALE$ is labels for x-axis values. It starts 2
1370           'spaces left of XAXIS$ and goes 2 spaces past.
1380 FOR X = XMIN TO XMAX STEP XINTERV
1390   POSITION = INT(70*(X-XMIN)/(XMAX-XMIN)) + 1
1400   'Place the I's in L$(1) to give axis tick marks
1410   L$(1) = LEFT$(L$(1),POSITION-1) + "I" + RIGHTS(L$(1),71-POSITION)
1420 '
1430   'Place the x-axis values in SCALE$ to show value at each tick mark
1440   POSITION = POSITION - INT(LEN(STR$(X))/2)
1450   IF POSITION < 1 THEN POSITION = 1      'Keep the values on the page
1460   IF POSITION > 76-LEN(STR$(X)) THEN POSITION = 76-LEN(STR$(X))
1470   SCALE$ = LEFT$(SCALE$,POSITION-1) + STR$(X) + RIGHTS(SCALE$,76-POSITION-LEN(STR$(X)))
1480 NEXT X
1490 L$(51) = L$(1)                  'Copy bottom axis into top axis
1500 '
1510 'Plot positions for the straight-line normal distribution based on the
1520 'mean and std dev. of the data
1530 FOR X = XMIN TO XMAX STEP (XMAX-XMIN)/100
1540   Z = (X-MEAN)/STDDEV
1550   YPOS = INT(26.5 + 10.74444*Z)          'Y plot position
1560   XPOS = INT(70*(X-XMIN)/(XMAX-XMIN)) + 1      'X plot position
1570   IF XPOS<1 OR XPOS>71 OR YPOS<1 OR YPOS>51 GOTO 1590 'Data pt.off plot
1580   L$(YPOS) = LEFT$(L$(YPOS),XPOS-1) + "/" + RIGHTS(L$(YPOS),71-XPOS)
1590 NEXT X
1600 '
1610 'Plot positions for the data points

```

```

1620 FOR I = 1 TO NPTS
1630     PROB = 1 - (I-.5)/NPTS      'Use NPTS+1 to plot all data points
1640     IF PROB <= .5 GOTO 1680      'Formulas only work for Prob(y) <= 0.5
1650     T = SQR(LOG(1/(1-PROB)^2))  'For Prob(y) > 0.5, use 1-Prob(y)
1660     PROBFLAG = -1
1670     GOTO 1700
1680     PROBFLAG = 1
1690     T = SQR(LOG(1/PROB^2))
1700     Z = T - ((2.515517+.802853*T+.010328*T^2)/(1+1.432788*T+.189269*T^2+.001308*T^3))
1710     Z = Z * PROBFLAG          'Correct Y for Prob(y) > 0.5
1720     YPOS = INT(26.5 - 10.74444*Z)    'Calculate Y position on plot
1730     XPOS = INT(70*(A(I)-XMIN)/(XMAX-XMIN)) + 1
1740     IF XPOS<1 OR XPOS>71 OR YPOS<1 OR YPOS>51 GOTO 1760  'Data pt.off plot
1750     L$(YPOS) = LEFT$(L$(YPOS),XPOS-1) + "0" + RIGHT$(L$(YPOS),71-XPOS)
1760 NEXT I
1770 '
1780 'Print main body of the Plot
1790 '
1800 SCALES$ = SPACES$(7) + SCALES$      'Add 7 spaces to the front of SCALES$
1810 LPRINT SPACES$(40-LEN(TITLE$)/2) + TITLE$      'Print data title centered
1820 LPRINT LEFT$(SCALES$,80)      'Be sure to print only 80 characters of SCALES$
1830 FOR I = 51 TO 1 STEP -1  'Line #51 at top descending to line #1 at bottom
1840     LPRINT YSCALE$(I);";L$(I)
1850 NEXT I
1860 LPRINT LEFT$(SCALES$,80)
1870 LPRINT
1880 RETURN
1890 '
1900 END

```

DISTRIBUTION LIST

	Copies
HQ ANGSC/SGB Mail Stop 18 Andrews AFB DC 20331-6008	1
HQ AFLC/SGBE Wright-Patterson AFB OH 45433-5001	1
HQ AFSC/SGPA Andrews AFB DC 20334-5000	1
HQ ATC/SGPB Randolph AFB TX 78150-5001	1
HQ MAC/SGPB Scott AFB IL 62225-5001	1
HQ TAC/SGPB Langley AFB VA 23665-5578	1
HQ SAC/SGPB Offutt AFB NE 68113-5001	1
HQ AFSPACEMCOM/SGB Peterson AFB CO 80914-5001	1
HQ PACAF/SGPB Hickam AFB HI 96853-5001	1
HQ USAFE/SGPA APO New York 09094-5001	1
HQ AFRES/SGB Robins AFB GA 31098-6001	1
HQ USAF/SGPA Bolling AFB DC 20332-6188	1
7100 CSW Medical Center/SGB APO New York 09220-5300	1
Det 3 AL APO San Francisco 96239-5000	1
USAFSAM/CC/BE/EH Brooks AFB TX 78235-5301	1 ea
Defense Technical Information Center (DTIC) Cameron Station Alexandria VA 22304-6145	2

Distribution List (continued)

AL/DOKLD
Brooks AFB TX 78235-5000

2